


NOTUS 19 LINEAR LED



TECHNICAL DETAILS

Housing :	Extruded aluminium
Diffuser :	Extruded PMMA
Control Gear :	Built-in electronic driver
Watt :	Max 131.2W
Transmittance :	70%
IP :	40
IK :	04
	• LED replacement with tools

Colors



-10
White



-20
Black



-90
Anoxal matt



-26
Copper

Accessories



CONVERSION
KIT+BATTERY



AUTO WIRE
SUPPORT BLOCK



DOUBLE SATIN
COVER



LINEAR OPAL
COVER



PRISMATIC
OPAL COVER

Lighting Sources


**1x Linear LED | CRI80**

3000K / 4000K |


3step MacAdam | Ripple < 3% | Lifetime>50.000h | LM80 test report

Lmax:4500mm

Lighting



Photometric



Headoffice - Showroom: 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece. Tel: +30 210 28 51 304 Fax: +30 210 28 51 306

Factory - Financial Services: 5 Kefalovrisou Str., Monomati, Aharnai, P.O. Box 13677 Athens, Greece. Tel: +30 210 62 08 230 Fax: +30 210 62 08 262

website: www.bright.gr | **e-mail:** info@bright.gr